

# ARA

## SINGLE GAS DETECTION



LOW MAINTENANCE, DISPOSABLE SINGLE  
GAS DETECTOR

[ionscience.com](https://ionscience.com)

Unrivalled Gas Detection<sup>ion</sup>.







ARA IS A PERSONAL, DISPOSABLE  
SINGLE GAS DETECTOR FOR  
H<sub>2</sub>S, CO, SO<sub>2</sub>, O<sub>2</sub> THAT PROVIDES  
INSTANTANEOUS ALARMS FOR  
LIFE-CRITICAL SAFETY SCENARIOS

Features

- 24 month or 36 month battery life options
- Easy to use with single button operation
- Live readings & instantaneous alarms to protect a users workforce in hazardous environments
- Event logging download
- Adjustable low & high alarms
- User-configurable calibration and bump test reminders
- Lifetime remaining countdown helps users to plan for future projects and site shutdowns

Ara IR Link\*

The IR Link enables ARA to communicate with a PC using infrared. The ARA PC allows users to download 30 recent event logs and configure user settings including:

- User ID
- Low alarm
- High alarm
- Displayed data (live reading or lifetime remaining)
- Calibration interval
- Bump Test interval
- Self Test interval

Self Test

ARA's self-test feature tests the audio, visual & vibrating alarms, giving users confidence that they are in safe hands. Easy to perform in a single button press and with user-configurable reminders, the self-test reassures users that their device is in safe working condition.

Industries

- Oil & gas
- Manufacturing
- Government & defence
- Water
- Aerospace
- Power generation

Applications

- Site wide safety
- Confined space entry
- Plant shutdown processes
- First response safety



ARA models available

The ARA has 6 different models

ARA Models	Model Number
Hydrogen Sulphide (H <sub>2</sub> S)	ARA100
Carbon Monoxide (CO)	ARA200
Oxygen (O <sub>2</sub> )	ARA300
Sulphur Dioxide (SO <sub>2</sub> )	ARA400
Hydrogen Sulphide (H <sub>2</sub> S) Hibernation Option	ARA100H
Carbon Monoxide (CO) Hibernation Option	ARA200H



Hibernation Mode

Hydrogen Sulphide and Carbon Monoxide models have a hibernation option available which extends the run time from 24 to 36 months. The hibernation models also come with an extended warranty period.



\*ARA IR link sold separately



## Technical specifications

### Sensor Type

- Single plug-in electrochemical cell

### Detection Range

- H<sub>2</sub>S: 0 to 100 ppm
- CO: 0 to 300 ppm
- SO<sub>2</sub>: 0 to 50 ppm
- O<sub>2</sub>: 0 to 25 %

### Event Log Storage

- Last 30 events

### Battery

- 3.6 Vdc, 1.65 Ah, lithium battery

### Battery Life

- Standard models: 24 months of operation (2 mins alarm per day)
- Hibernation models: 36 months of operation (2 mins alarm per day and using sleep function)

### Approvals

- Ratings: Class I, Division 1, Groups A, B, C and D, T4; Class I, Zone 0, AEx ia IIC T4 Ga; Ex ia IIC T4 Ga; -40 °C ≤ Ta ≤ +60 °C: ARA100, ARA200, ARA400, ARA100H, ARA200H -30 °C ≤ Ta ≤ +60 °C: ARA300
- Applicable Standards: CAN/CSA C22.2 No. 60079-0:19 CAN/CSA C22.2 No. 60079-11:14 ANSI/UL 60079-0 7th ed. ANSI/UL 60079-11 6th ed

### User Options

- User ID
- Low alarm
- High alarm
- Displayed data (live reading or lifetime remaining)
- Bump-Test interval
- Calibration interval
- Self-Test interval

### Alarms

- Audio Alarm: (95 dB @ 10 cm)
- Visual Alarm: LED
- Vibrating Alarm: Vibrator (Operates at ±10 °C)

### Temperature

- H<sub>2</sub>S, CO, SO<sub>2</sub>: - 40 °C to + 60 °C
- O<sub>2</sub>: - 30 °C to + 60 °C
- Humidity: 5 - 95 % RH

### Ingress Protection

- IP67

### Display

- Liquid Crystal Display (LCD)

### Weight & dimensions

- 92 g (3.2 oz)
- 87 x 50 x 29 mm (3.4 x 2.0 x 1.1 inch)

ARA V1.0. This publication is not intended to form the basis of a contract and specifications can change without notice.

## Distributed by:

### ION Science Ltd

The Hive, Butts Lane,  
Fowlmere,  
Cambridgeshire,  
SG8 7SL, UK

T +44 (0)1763 208503

E [info@ionscience.com](mailto:info@ionscience.com)